

SPA WINTERIZING GUIDE

A step-by-step checklist to help protect your spa during winter storage

01 | Shut down & drain

1	Turn OFF power to the spa at the electrical supply.
2	Drain the spa completely, loosen the pump unions, and remove the pump drain plugs.
3	Use a wet/dry vacuum (suction or air-discharge function) at the discharge to clear remaining water.
4	Remove the suction connection from the pump and blow air through it as well.
5	For spas with multiple pumps, repeat the pump-draining and air-clearing process for each pump.
6	Loosen the heater union and allow the heater to drain.
7	Reconnect the heater and pump unions, and reinstall the pump drain plugs after all remaining water has drained.
8	Use the wet/dry vacuum to remove remaining water from the spa interior.

02 | Finish & protect

9	Remove and clean the filter using a filter soak. The cleaned filter may be stored in the spa for winter.
10	Install the hard cover and secure a tarp over it. Prevent water, snow, and ice from entering the spa or reaching equipment beneath the cabinet.

IMPORTANT WINTER REMINDER

Keep snow cleared off the spa cover. Heavy accumulation can cause the hard cover to collapse.

These are basic winterizing guidelines. For detailed questions or model-specific procedures, contact a qualified local spa professional.

USA Spas • www.usaspas.net • 888-729-7727